



SHELLEVIS®



PRODUCT SPECIFICATIONS

**SHELLEVIS®
POOL COPINGS**

Schellevis® swimming pool copings makes sure that a swimming pool flows seamlessly over in the pool deck, creating a beautiful finish. The swimming pool coping is rounded and non-slip, creating a safe and luxurious surround to every swimming pool.

You can choose from two different sizes and a variety of grey tints for the swimming pool copings and corners. Thanks to the recognisable traditional Dutch appearance and structure, the swimming pool copings can easily be combined with other products in the Schellevis® range.

Combining the best of natural raw materials and colouring agents with a special production process and Dutch craftsmanship gives the swimming pool edging its unique and timeless character.

GUIDED BY NATURE

We believe it's important that an outdoor space is well-balanced and exudes tranquillity. Because in a living environment like that, you can relax; you're in your element, enjoying it. Whether alone or together with others. The outdoor space is the Schellevis® domain and nature is a major source of inspiration. We connect architecture with nature, with respect for the environment. That's how we contribute to a sustainable, natural experience of the outdoor space

PRODUCT SPECIFICATIONS SCHELLEVIS® POOL COPINGS

LxBxH in mm	Type	Kg	# copings per pallet	Pallet size in mm	Reinforced	Colours
1000x400x50		43	20	1000x800	✓	● ● ● ● ●
1000x1000x50		109	10	1000x1000	✓	● ● ●
1000x400x50	Miter Corner piece left	17	20	1000x800	✓	● ● ● ● ●
1000x400x50	Miter Corner piece right	17	20	1000x800	✓	● ● ● ● ●
1000x1000x50	Corner piece	108	10	1000x1000	✓	● ● ●

Product features

- Unique Schellevis® structure and appearance
- Rounded corners on the inside
- Chlorine resistant
- Products taper (1.5 mm each side)
- No bevel
- Durable due to the use of natural raw materials and colouring agents
- Non-slip
- Resistant to frost and road salt
- Country of origin: The Netherlands
- Material type: Concrete

Technical features



- Dimensional stability - diagonal ≤ 850 mm: ≤ 3 mm
- Dimensional stability - diagonal ≥ 850 mm: ≤ 6 mm
- Dimensional stability (L/B) ≤ 600 mm is: ± 2 mm, (D) ± 3 mm
- Dimensional stability (L/B) ≥ 600 mm is: ± 3 mm, (D) ± 3 mm
- Flexural strength: $\geq 5,0$ N/mm²
- Wear resistance: ≤ 23
- Environmental class: XF4
- Slip resistance: R13
- Reaction to fire: NPD
- Weather resistance (frost/thaw): 0,2 kg/m²

Processing instructions

- Both the top and side can be placed in sight since both are provided with the characteristic Schellevis® structure.
- Use joint of at least 5 mm when placing the products. The larger the product, the broader the joint (maximum 10 mm).
- Lay the products on a bed that is stable, level and draining. That way, the products will be well anchored and you will prevent subsidence.
- Don't use a vibrating compacter but use a rubber mallet instead.
- There may be a natural variation in structure or colour in each batch. This variation is due to the production process and is part and parcel of the natural character of the product.
- It's therefore advisable to mix the products from several pallets when processing.

Schellevis® quality

- NL BSB certificate K20627
- KOMO certificate / Kiwa K79475
- CSC mark (Concrete Sustainability Council)
- NL Greenlabel



SCHELLEVIS®