

PRODUCT SPECIFICATIONS

**SHELLEVIS®
SPECIAL SHAPE
SLABS**

For those looking for something just a little bit different, Schellevis® special shape slabs are the perfect choice. They make it possible for you to pave your outdoor space in a creative way, using an unusual element that catches the eye. You can make straight or round passageways with a playful touch. Give your imagination free rein and discover the endless possibilities that Schellevis® special shape slabs have to offer in bringing your outdoor space to life

The trapezium slabs are available in 120x30/60/8 cm. The round slabs are available in 60x7 cm, 80x7 cm and 100x8 cm. With regard to colour, both the trapezium and the round slabs are available in grey or anthracite. Thanks to the distinctive Schellevis® traditional Dutch look, the trapezium and round slabs can be perfectly combined with other products from the Schellevis® range.

GUIDED BY NATURE









We believe it's important that an outdoor space is well-balanced and exudes tranquillity. Because in a living environment like that, you can relax; you're in your element, enjoying it. Whether alone or together with others. The outdoor space is the Schellevis® domain and nature is a major source of inspiration. We connect architecture with nature, with respect for the environment. That's how we contribute to a sustainable, natural experience of the outdoor space

PRODUCT SPECIFICATIONS SCHELLEVIS® SPECIAL SHAPE SLABS

Trapezium slabs

LxBxH in mm	Kg	Safe load in a sand bed (kg)	Safe load on 4 corners (kg)**	#slabs per m²	#slabs per pallet	Pallet size in mm	Colours	Reinforced	Can be used for
1200x300/600x80	98	750	550	1,85	16	2000x1200	 	✓	 

Round Slabs

Ø600x70	45	4500	-	0,28	16	1200x600	 		 
Ø800x70	79	3500	-	0,50	8	930x930	 	✓	 
Ø1000x80	142	2750	-	0,79	8	1000x1000	 	✓	 

* Safe load permitted per tile in a sand bed of > 200 mm and a wheel surface area of 250x250 mm

** Safe load permitted per tile laid on 4 corners. Minimum size bearing block 30x30x4 mm and wheel surface area of 250x250 mm.

Product features

- Unique Schellevis® structure and appearance
- Products taper (1.5 mm each side)
- No bevel
- Durable due to the use of natural raw materials and colouring agents
- Non-slip
- Resistant to frost and road salt
- Country of origin: The Netherlands
- Material type: Concrete

Technical features

- Dimensional stability (L/B):
≥ 600 mm: ± 3 mm, (D) ± 3 mm
- Dimensional stability – diagonal:
≥ 850 mm: ≤ 6 mm
- Flexural strength: ≥ 5,0 N/mm²
- Wear resistance: ≤ 23
- Environmental class: XF4
- Slip resistance: R13
- Reaction to fire: NPD
- Weather resistance (frost/thaw): 0,2 kg/m²

Processing instructions


- Both the top and side can be placed in sight since both are provided with the characteristic Schellevis® structure.
- Use joint of at least 5 mm when placing the products. The larger the product, the broader the joint (maximum 10 mm).
- Lay the products on a bed that is stable, level and draining. That way, the products will be well anchored and you will prevent subsidence.
- Don't use a vibrating compacter but use a rubber mallet instead.
- There may be a natural variation in structure or colour in each batch. This variation is due to the production process and is part and parcel of the natural character of the product.
- It's therefore advisable to mix the products from several pallets when processing.

Schellevis® quality

- Tested according to European standards: EN 1339
- NL BSB certificate K20627
- CE certificate and DoP 530
- CSC mark (Concrete Sustainability Council)
- NL Greenlabel



Grey



Anthracite



SCHELLEVIS®