

## Level 3 DC Fast Chargers – 50kW

Powerful and convenient Level 3 DC Fast Chargers

- Market favorite
- Simple and reliable design
- Ideal size for most opportunity charging



### 50 kW DC chargers

	LEDC-B50LV-208V-PDC-EXXRX	LEDC-B50LV-480V-PDC-EXXRX	LEDC-B50LV-208V-PDD-EXXRX	LEDC-B50LV-480V-PDD-EXXRX
<b>Output power</b>	50 kW (dual port)	50 kW (dual port)	50 kW (dual port)	50 kW (dual port)
<b>Mount</b>	Pedestal	Pedestal	Pedestal	Pedestal
<b>Cable length</b>	Dual 18ft cables	Dual 18ft cables	Dual 18ft cables	Dual 18ft cables
<b>Input Power</b>	208V / 166A three-phase	480V / 72A three-phase	208V / 166A three-phase	480V / 72A three-phase
<b>Connectors</b>	2 x J1772 CCS-1 Combo	2 x J1772 CCS-1 Combo	J1772 CCS-1 Combo & CHAdeMO	J1772 CCS-1 Combo & CHAdeMO
<b>Maximum output voltage</b>	500V			

<b>Display</b>	15" touch screen
<b>Dimensions</b>	34" W x 86" H x 22" D
<b>Weight</b>	850 lbs
<b>Card reader</b>	Ethernet
<b>Network</b>	RFID
<b>Communication protocol</b>	OCPP
<b>Electrical protection</b>	Surge Protection: 6000 VAC
<b>Regulatory compliance</b>	ETL Listed for USA and Canada: Complies with UL 2202, UL 2231 UL50E, NEC Article 625, CSA STD C22.2 No. 107.1, FCC Part 15 Class A
<b>Operating temperature</b>	-30 °C to +50 °C
<b>Options</b>	Credit card reader, cable retractor, 3G/4G modem
<b>Warranty</b>	2 years, parts only