

Q50 - Site/ Street Furniture/ Equipment

Site and Street Furniture

To be read with Preliminaries/ General conditions.

221 Seating Elements:

1. Manufacturer: Schellevis® BV
Address: Loswal 11, Dussen, 4271 BA, Netherlands
Telephone: 07960988327 (Ryan Burge - UK Sales Manager)
Email: ryan@schellevis.co.uk
Website: schellevis.co.uk
 - 1.1. Product reference: *Please refer to standard assortment, or speak with Schellevis® regarding bespoke options.*
2. Material: Schellevis®
 - 2.1. Finish: Schellevis® Finish ("broken basalt / lava effect" on top and 4 sides)
 - 2.2. Profile: Standard 10mm pencil round to all top edges, unless stated otherwise
 - 2.3. Colour: Choose from standard assortment (or speak with Schellevis®) - Samples to be provided for approval if required.
 - 2.4. Properties of the product:
 - 100% the same concrete composition (through and through colour)
 - Made with 50% recycled concrete granulate and 5% eco sand
 - Tiles are tapered outwards from the top face (1.5 mm per side)
 - Concrete quality minimum C35/45
 - Product certificate NL BSB® according to BRL 5070 KIWA
 - CSC concrete quality mark
 - CE certificate and DoP 530
 - 100% recyclable
 - NL Greenlabel
 - Quality according to EN 1339
 - Flexural strength: $\geq 5,0$ N/mm²
 - Wear resistance: ≤ 23
 - Environmental class: XF4
 - Slip resistance: R13
 - Reaction to fire: NPD
 - Weather resistance (frost/thaw): 0.2 kg/m²
 - Country of origin: The Netherlands
 - Other technical characteristics: see art.
3. Size: *Please refer to standard assortment, or speak with Schellevis® regarding bespoke options.*
4. Accessories/ Special requirements: 150mm Thickness Base Plates available for Seating Elements, to create additional height and shadow gap features. Please discuss with Schellevis® directly for special requirements.
5. Method of fixing: To be agreed with Schellevis® and Landscape Architect.

6. Cutting: All cuts must be made with water suppression, in line with H&S standards. Any cut pieces must be immediately cleaned with freshwater, to avoid staining.
7. Jointing: *Please speak with Schellevis® for jointing material options.*