


NKODA™
WE ARE PPF



PPF Product Specifications

NKODAGLOBAL.COM

NKODA.SHOP

NKODA™


**THE
PINNACLE
OF PROTECTION**

XDI **NEX
GEN
PPF**




Say goodbye to *temperature distortion*

Model	XDI	Tensile Strength	42 Mpa	
Material	TPU	Tear Strength	98 KN/m	
Effect	High Gloss	Elongation at Break	≥420%	
Size	1.52*15	100% Modulus	7.4 Mpa	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	Anti-yellowing	ΔE < 12.8	
Thickness	8 mil / 200 UM	Hydrophobic Property	RIO	
Self-Healing Thickness	16 UM	Peeling Force of Acrylic Adhesive layer	20min	24h
Base Film Thickness	160um±8		1763 gf/inch	2308 gf/inch
Adhesive Thickness	25 UM	Durability	Zone 1	Zone 2
Gloss	95.4		Lifetime	Lifetime



IMPACT SERIES
PRO

- Ultra Gloss Enhancing
- Self-Healing W/Heat
- Non-Yellowing
- Mid-initial Tack
- Max Stretchability




Model	PRO	
Material	TPU	
Effect	High Gloss	
Size	60" x 50' · 1.52*15M	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	8 mil / 200 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	97	
Tensile Strength	33.9Mpa	
Tear Strength	65.1KN/m	
Elongation at Break	≥430%	
100% Modulus	6.9Mpa	
Anti-yellowing	ΔE< 1	
Hydrophobic Property	>R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	937 gf/inch	1498 gf/inch
Durability	Zone 1	Zone 2
	Lifetime	Lifetime



Model	PRO WIDE
Material	TPU
Effect	High Gloss
Size	1.83*15M
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating

IMPACT SERIES
PRO WIDE

- Ultra Gloss Enhancing
- Self-Healing W/Heat
- Non-Yellowing
- Mid-initial Tack
- Max Stretchability




Thickness	8 mil / 200 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	97	
Tensile Strength	33.9Mpa	
Tear Strength	65.1 KN/m	
Elongation at Break	≥430%	
100% Modulus	6.9Mpa	
Anti-yellowing	ΔE< 1	
Hydrophobic Property	> R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	937 gf/inch	1498 gf/inch
Durability	Zone 1	Zone 2
	Lifetime	Lifetime



IMPACT SERIES
FORCE

- Self-Healing W/Heat
- Non-Yellowing
- Low-initial Tack
- Good Stretchability




Model	FORCE	
Material	TPU	
Effect	High Gloss	
Size	1.52*15M	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	7.5 mil / 190 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	94.6	
Tensile Strength	23.66Mpa	
Tear Strength	86.1KN/m	
Elongation at Break	≥325%	
100% Modulus	9.14Mpa	
Anti-yellowing	ΔE< 1.2	
Hydrophobic Property	>R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1272 gf /inch	2525 gf /inch
Durability	Zone 1	Zone 2
	5 Years	3 Years



Model	OFF-ROAD¹²
Material	TPU
Effect	High Gloss
Size	1.52*15M
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating

IMPACT SERIES
OFF-ROAD¹²

- Ultra Gloss Enhancing
- Self-Healing W/Heat
- Non-Yellowing
- Mid-initial Tack




Thickness	12 mil / 300 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	270um±8	
Adhesive Thickness	25 UM	
Gloss	95.3	
Tensile Strength	21.7Mpa	
Tear Strength	72.3 KN/m	
Elongation at Break	≥400%	
100% Modulus	9.14Mpa	
Anti-yellowing	ΔE< 1.2	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1783 gf/inch	2325 gf/inch
Durability	Zone 1	Zone 2
	10 Years	7 Years

NKODA™



IMPACT SERIES
SATIN

- Self-Healing W/Heat
- Non-Yellowing
- Mid-initial Tack
- Excellent Stretchability



Model	SATIN	
Material	TPU	
Effect	High Gloss	
Size	1.52*15M	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	7.5 mil / 190 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	18.7	
Tensile Strength	23.66Mpa	
Tear Strength	60.3 KN/m	
Elongation at Break	≥375%	
100% Modulus	23.7Mpa	
Anti-yellowing	ΔE< 1.5	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	2144 gf/inch	2378 gf/inch
Durability	Zone 1	Zone 2
	10 Years	7 Years




Model	CLEARVIEW
Material	TPU
Effect	High Gloss
Size	1.82*15M
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating

IMPACT SERIES
CLEARVIEW
 WINDSHIELD PPF

- 100% TPU (no polycarbonate)
- Specifically Formulated Windshield Clarity
- Mid-initial Tack
- Heat Rejecting

Thickness	8 mil / 200 UM
Self-Healing Thickness	16 UM
Base Film Thickness	150um±8
Adhesive Thickness	20 UM
Gloss	98
Tensile Strength	29 Mpa
Tear Strength	62 KN/m
Elongation at Break	180%

100% Modulus	7.16 Mpa	
Anti-yellowing	ΔE< 1	
Hydrophobic Property	> R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1592 gf/inch	2135 gf/inch
Durability	Zone 1	Zone 2
	2 Years	2 Years






Model	LUMINA
Material	TPU
Effect	High Gloss
Size	1.82*15M
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating

IMPACT SERIES LUMINA GLOW PPF

- 100% TPU (no polycarbonate)
- Specifically Formulated Windshield Clarity
- Mid-initial Tack
- Heat Rejecting



Thickness	8 mil / 200 UM	
Self-Healing Thickness	16 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	94.8	
Tensile Strength	29 Mpa	
Tear Strength	69 KN/m	
Elongation at Break	≥360%	
100% Modulus	7.16 Mpa	
Anti-yellowing	ΔE< 1	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1592 gf/inch	2135 gf/inch
Durability	Zone 1	Zone 2
	8 years	8 years




Model	SL 7.5
Material	TPU
Effect	High Gloss
Size	1.52*15M
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating

BLUE LINE SL 7.5

- Ultra Gloss Enhancing
- Self-Healing W/Heat
- Non-Yellowing
- Mid-initial Tack
- Max Stretchability

Thickness	7.5 mil / 190 UM	
Self-Healing Thickness	16 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	94.5	
Tensile Strength	24 Mpa	
Tear Strength	86 KN/m	
Elongation at Break	≥310%	
100% Modulus	9.16 Mpa	
Anti-yellowing	ΔE< 1.2	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1272 gf/inch	2485 gf/inch
Durability	5 years	






Model	SL 6.5
Material	TPU
Effect	High Gloss
Size	1.52*15M
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating

BLUE LINE SL 6.5

- Ultra Gloss Enhancing
- Self-Healing W/Heat
- Non-Yellowing
- Mid-initial Tack
- Max Stretchability



Thickness	6.5 mil / 170 UM
Self-Healing Thickness	18 UM
Base Film Thickness	130um±8
Adhesive Thickness	25 UM
Gloss	94.3
Tensile Strength	22 Mpa
Tear Strength	98 KN/m
Elongation at Break	≥300%
100% Modulus	9.30 Mpa

Anti-yellowing	ΔE< 1.2
Hydrophobic Property	R9-R10
Peeling Force of Acrylic Adhesive layer	20min
	24h

1245 gf/inch	1778 gf/inch
--------------	--------------

Durability	5 years
------------	---------


NKODA™



Model	HL 7.5	
Material	TPU	
Effect	High Gloss	
Size	1.52*15M	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	7.5 mil / 190 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	94.4	
Tensile Strength	23.66 Mpa	
Tear Strength	85.1KN/m	
Elongation at Break	≥300%	
100% Modulus	9.14 Mpa	
Anti-yellowing	ΔE< 1.2	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1262 gf/inch	2485 gf/inch
Durability	3 years	

BLUE LINE
HL 7.5

- Ultra Gloss Enhancing
- Self-Healing W/Heat
- Non-Yellowing
- Mid-initial Tack
- Max Stretchability






Model	HL 6.5	
Material	TPU	
Effect	High Gloss	
Size	1.52*15M	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	6.5 mil / 170 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	130um±8	
Adhesive Thickness	25 UM	
Gloss	94.2	
Tensile Strength	21.62 Mpa	
Tear Strength	97.69 KN/m	
Elongation at Break	≥290%	
100% Modulus	9.28 Mpa	
Anti-yellowing	ΔE< 1.2	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1235 gf/inch	1778 gf/inch
Durability	3 years	

BLUE LINE HL 6.5

- Ultra Gloss Enhancing
- Self-Healing W/Heat
- Non-Yellowing
- Mid-initial Tack
- Max Stretchability






Model	SHADES	
Material	TPU	
Effect	High Gloss	
Size	1.52*15	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	8 mil / 200 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	160um±8	
Adhesive Thickness	25 UM	
Gloss	96	
Tensile Strength	27.8 Mpa	
Tear Strength	68.2 KN/m	
Elongation at Break	≥400%	
100% Modulus	6.8 Mpa	
Anti-yellowing	ΔE< 1	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	2057 gf/inch	2411 gf/inch
Durability	Zone 1	Zone 2
	10 years	7 years

VIBE NANO COLOR PPF

SHADES

- Restoration brightening coating
- Nano ceramic material super dispersion top coat
- TPU base film
- High Performance Adhesive Layer

TrueFusion™
Color TPU Technology






Model	CLASSICS	
Material	TPU	
Effect	High Gloss	
Size	152*15M	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	8 mil / 200 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	160um±8	
Adhesive Thickness	25 UM	
Gloss	92.8	
Tensile Strength	27.8 Mpa	
Tear Strength	70.4 KN/m	
Elongation at Break	≥400%	
100% Modulus	7.2 Mpa	
Anti-yellowing	ΔE<1	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1301 gf/inch	1923 gf/inch
Durability	Zone 1	Zone 2
	10 years	7 years

VIBE NANO COLOR PPF CLASSICS

- Restoration brightening coating
- Nano ceramic material super dispersion top coat
- TPU base film
- High Performance Adhesive Layer

TrueFusion™ Color TPU Technology






Model	SPECIALS	
Material	TPU	
Effect	High Gloss	
Size	1.52*15M / 0.76*15M	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	8 mil / 200 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	92.8	
Tensile Strength	24.1Mpa	
Tear Strength	58.4 KN/m	
Elongation at Break	≥350%	
100% Modulus	6.7 Mpa	
Anti-yellowing	ΔE< 1.5	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1152 gf/inch	1848 gf/inch
Durability	Zone 1	Zone 2
	10 years	7 years

VIBE NANO COLOR PPF SPECIALTY

- Restoration brightening coating
- Nano ceramic material super dispersion top coat
- TPU base film
- High Performance Adhesive Layer

TrueFusion™ Color TPU Technology





SHADES



Ghost White



Black Mirror



Pitch Black (Satin)

CLASSICS



Mars Red



Purple Rain



Stainless Steel



Clockwork Orange



Little Red Wagon



Tiffany Blue



Amazon Jungle



Tuscan Sun



Sparkling Emerald Green



Silver 925



Shadow Grey




Frosted White



Barbie Pink



Mauve-oulous



Dusty Rose



Blue Lagoon

SPECIALTY




Iridescent Blue Ice



Iridescent Watermelon



Iridescent Terra Firma



Iridescent Purple Magic


NKODA™



VAPOR
HEAD/TAIL LIGHT

30%
50%
70%

- Simple to install Headlight and Taillight Film



Model	VAPOR	
Material	TPU	
Effect	High Gloss	
Size	1.52*15M / 0.76*15M	
Warranty Coverage	Yellowing, Staining, Cracking, Blistering, Delaminating	
Thickness	8 mil / 200 UM	
Self-Healing Thickness	15 UM	
Base Film Thickness	150um±8	
Adhesive Thickness	25 UM	
Gloss	92.8	
Tensile Strength	24.1 Mpa	
Tear Strength	58.4 KN/m	
Elongation at Break	≥350%	
100% Modulus	6.7 Mpa	
Anti-yellowing	ΔE< 1.5	
Hydrophobic Property	R9-R10	
Peeling Force of Acrylic Adhesive layer	20min	24h
	1152 gf/inch	1848 gf/inch
Durability	Zone 1	Zone 2
	10 years	7 years