



Level 2 AC Chargers – 7.2 kW and 9.6 kW

Cost-effective and space-saving Level 2 chargers

- Minimal installation requirements
- Cost-effective
- Compact design

7.2 kW AC chargers

	LEAC-B7200-30A-WSA-EXXR	LEAC-B7200-30A-PSA-EXXR	LEAC-B7200-30A-WDA-EXXR	LEAC-B7200-30A-PDA-EXXR
Output power	7.2 kW (single port)	7.2 kW (single port)	7.2 kW (dual port)	7.2 kW (dual port)
Mount	Wallbox	Pedestal	Wallbox	Pedestal
Cable length	Single 25ft cable	Single 25ft cable	Dual 25ft cables	Dual 25ft cables
Input power	208V / 240V, 30A service, 40A breaker			

9.6 kW AC chargers

	LEAC-B9600-40A-WSA-EXXR	LEAC-B9600-40A-PSA-EXXR	LEAC-B9600-40A-WDA-EXXR	LEAC-B9600-40A-PDA-EXXR
Output power	9.6 kW (single port)	9.6 kW (single port)	9.6 kW (dual port)	9.6 kW (dual port)
Mount	Wallbox	Pedestal	Wallbox	Pedestal
Cable length	Single 25ft cable	Single 25ft cable	Dual 25ft cables	Dual 25ft cables
Input power	208V / 240V, 40A service, 50A breaker			

Connector type	SAE J1772
Display	7" color display
Card reader	RFID
Network	Ethernet
Communication protocol	OCPP
Electrical protection	Ground fault detection: 20 mA
Enclosure rating	NEMA 3R
Regulatory compliance	ETL Certified for USA and cUL Certified for Canada; Complies with UL 2594, UL 2231-1, UL 2231-2, and NEC Article 625, EMC: FCC Part 15 Class A
Operating temperature	-30°C to +60°C (-22°F to 140°F)
Options	Credit card reader, cable retractor, 3G/4G modem
Warranty	2 years, parts only