



## Level 3 DC Fast Chargers – 120kW

Powerful and convenient Level 3 DC Fast Chargers

- HV compatible
- Simultaneous dynamic vehicle charging
- Modular design for improved serviceability
- All-in-one unit



### 120 kW DC chargers

	LEDC-T120MV-480V-PDD-EWCRX	LEDC-T120MV-480V-PDC-EWCRX	LEDC-T120HV-480V-PDD-EWCRX	LEDC-T120HV-480V-PDC-EWCRX
<b>Output power</b>	120 kW (dual port)	120 kW (dual port)	120 kW (dual port)	120 kW (dual port)
<b>Mount</b>	Pedestal	Pedestal	Pedestal	Pedestal
<b>Cable length</b>	Dual 16ft cables	Dual 16ft cables	Dual 16ft cables	Dual 16ft cables
<b>Connector type(s)</b>	J1772 CCS-1 Combo & CHAdeMO	J1772 CCS-1 Combo x 2	J1772 CCS-1 Combo & CHAdeMO	J1772 CCS-1 Combo x 2
<b>Maximum output voltage</b>	750 V	750 V	1000 V	1000 V
<b>Input Power</b>	480V / 160A, 200A breaker, three phase			

<b>Display</b>	7" touch screen
<b>Dimensions</b>	29" x 26.5" x 72"
<b>Weight</b>	840 lbs (380kg)
<b>Card reader</b>	RFID
<b>Network</b>	Ethernet
<b>Wifi</b>	Yes
<b>4G capable</b>	Yes
<b>Communication protocol</b>	OCPP
<b>Electrical protection</b>	RCD 20 mA Type A. Over Voltage, Under Voltage, Over Current, Missing Ground
<b>Enclosure rating</b>	NEMA 3S, IK10
<b>Regulatory compliance</b>	UL-2202    EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012
<b>Operating temperature</b>	-22°F to 131°F (-30°C to 55°C)
<b>Options</b>	Credit card reader, cable retractor, 3G/4G modem
<b>Warranty</b>	2 years, parts only