

Level 2 AC Chargers – 9.6 kW and 11.5 kW

Compact and flexible Level 2 chargers

- Minimal installation requirements
- “Hub” style connectivity available
- Cost effective
- Multi-mount pole available
- Ideal solution for most overnight fleet charging needs



9.6 kW AC chargers

	LEAC-S9600-40A-WSA-XXXXX	LEAC-S9600-40A-WSA-EWXXX	LEAC-S9600-40A-WSA-EWXRX	LEAC-S9600-40A-WSA-EWCRX
Output power	9.6 kW (single port)	9.6 kW (single port)	9.6 kW (single port)	9.6 kW (single port)
Mount	Wallbox			
Cable length	Single 20ft cable			
Network	None	Ethernet	Ethernet	Ethernet
WiFi	No	Yes	Yes	Yes
4G	No	No	No	Yes
Card reader	None	None	RFID	RFID
Input power	208V / 240V, 40A service, 50A breaker			

11.5 kW AC chargers

	LEAC-S11500-48A-WSA-XXXXX	LEAC-S11500-48A-WSA-EWXXX	LEAC-S11500-48A-WSA-EWXRX	LEAC-S11500-48A-WSA-EWCRX
Output power	11.5 kW (single port)	11.5 kW (single port)	11.5 kW (single port)	11.5 kW (single port)
Mount	Wallbox			
Cable length	Single 20ft cable			
Network	None	Ethernet	Ethernet	Ethernet
WiFi	No	Yes	Yes	Yes
4G	No	No	No	Yes
Card reader	None	None	RFID	RFID
Input power	208V / 240V, 48A service, 60A breaker			

Specifications common to all models

Connector type	SAE J1772
Dimensions	446 mm x 180 mm x 158 mm
Weight	Cable: 1~5,3kg; 3~7.2kg / socket: 1~2.9kg; 3~5.0kg
Communication protocol	Ocpp
Electrical protection	Current +10% above configured threshold, min. +2 A / 5 seconds
Enclosure rating	IP56 and IK10
Regulatory compliance	EN IEC 61851-1, EN IEC 61851-21-2, EN IEC 60068-2-52, EN IEC 61000-6-1, EN 61000-6-3, EN IEC 61000-6-4, EN 330 330, EN 300 328, EN 301 511, EN 301 893, IEC 62955
Operating temperature	-30°C to +50°C
Options	Credit card reader, cable retractor, 3G/4G modem, post mount
Warranty	2 years, parts only



January 2022. The information presented here may be subject to change at any time.

© 2022 Lightning eMotors

charging@lightningemotors.com

+1 970-744-4948

lightningemotors.com/energy